





Anchorwall is a **fixed part-height steel partition** available in a **single skin, double skin, mesh or perforated finish**.

Typically used in **manufacturing, production** and **warehouse environments**, it is a robust and sturdy long term solution when dividing open areas and creating enclosed work areas. It can also be reconfigured and/or relocated as business needs change.



Fixed Steel Partition wall



Minimal Floor Space Required



Range of Finishes



Range of Panel Sizes



Door Options and Accessories



Fire Rated Panels on Request



Features and Benefits

Panels are custom-made to project requirements	<ul style="list-style-type: none"> • Modular design and bespoke panels allows for flexible installations • Anchorwall system can be tailored to suit project requirements
Can be used multi-tier to suit various applications	<ul style="list-style-type: none"> • Create part-height or floor-to-ceiling partitions
Comprehensive range of accessories, door and glazing options available	<ul style="list-style-type: none"> • Create a customised solution to meet your requirements • Design, installation and project management all managed in house
Electrostatically powder coated panels available in a range of colours	<ul style="list-style-type: none"> • Panels manufactured to suit your environment, with a range of finishes
Single or double skin panel options	<ul style="list-style-type: none"> • Single skin offers a lightweight cost effective alternative when only a smooth finish is required to one side • Double skin offers better fire ratings and seamless finish on both sides
Fire rated (double skin only on request) and sound reducing (double skin only)	<ul style="list-style-type: none"> • Double skin panels can be supplied in a fire-rated version to BS476: Part22:1987 on request* Double skin panels offer noise reduction between 28db – 32db (Please note the mesh and single skin options do not have fire ratings or sound reduction)
Insulated (on request)	<ul style="list-style-type: none"> • As typical, panels are not insulated, however the double skin can be supplied with insulation on request



This fact sheet is for illustrative purposes only and based on the latest information at the time of print. Installation methods may vary depending on specific project requirements. Westgate Global reserve the right to make changes at any time without notice.

J332-WDF-PFS-AW-010323 © Westgate Global Ltd

Technical Specifications

Panel Composites	full steel; steel/glass/steel; steel/glass; fully glazed; steel/mesh/steel
Paint Finishes	electrostatically powder coated in the following standard colours; light/medium/dark grey; sandstone; white; stone
Typical Panel Heights	between 2400mm – 3000mm
Panel Widths	1000mm
Panel Thickness	between 43mm – 47mm (mesh constructed from weld mesh 50x50x3mm (10g) spot welded to frame)
Fire Rating and Sound Reduction	double skin option can be supplied in a fire-rated version to BS476: Part22:1987 on request* Noise reduction between 28db – 32db

Anchorwall can be used as a fixed solid partition to; subdivide storage areas, create site offices and clean rooms, separate different operational processes or machines/equipment, product segregation for security (e.g chemicals and liquids etc). Can also be used part-height to create a solid base, with Flexiwall above to deliver a floor-to-ceiling partition wall.

