

Flexidoor®

pvc crash door



Technical Specifications

Standard Frame Options	43mm O/D 32mm tube to BS1387, 50mm x 5mm mild steel <small>(*heavy duty options available; speak to your sector manager)</small>
Frame Finish	Primer, powder coat, zinc spray finish
Panels	Rubber 8mm thickness. Flexible PVC up to 7mm thickness.

Flexidoor **hinged crash doors** offer a **practical** and **economical** two way crash swing door to accompany Westgate's range of partitioning solutions.

Quick and **unrestricted access** reduces heat loss, noise pollution, dust ingress and cross contamination.



Control Temperature



Reduce Cross Contamination Risk



Install as part of an Integrated Solution

Features and Benefits

Bespoke door panel designs and configurations available	<ul style="list-style-type: none"> In heavy usage areas we recommend rubber panels, which supply high impact resistance and low abrasive wear Suit visibility requirements and traffic type
Can be used with our range of partitioning products to provide an integrated solution	<ul style="list-style-type: none"> Used with Hoardfast to create contamination free zones Used with Flexiwall or Anchorwall to create access doorways
Can be used in multiple environments and for multiple applications	<ul style="list-style-type: none"> Retain temperature in cold stores Quick access in retail stores between store and storage Where self-closing doors are required in heavy usage areas
Can be supplied in PVC and aluminium frame	<ul style="list-style-type: none"> For environments requiring a food grade solution

This fact sheet is for illustrative purposes only and based on the latest information at the time of print. Installation methods may vary depending on specific project requirements. Westgate Global reserve the right to make changes at any time without notice.

J335-WFD-FD-010323 © Westgate Global Ltd